

# H902GPSF Board

H902GPSF is a 16-port GPON OLT interface board, which works together with the ONU to implement GPON access services.



## Benefits

- **High density and energy-conversation**
  - High density and low power consumption, supporting access of 2048 users
- **High reliability**
  - Chip-level type B protection (single-homing) and type C protection (single-homing) switching
  - Real-time rogue ONT detection and isolation, ensuring stable service running
- **Easy OAM**
  - Variable-length OMCI, improving upgrade efficiency and reducing break off time
  - A maximum distance difference of 40 km between two ONUs under the same PON port (board capability), simplifying network planning

## External Interfaces

### 16 GPON ports (SFP)

- Maximum split ratio
  - Class B+: 1:64
  - Class C+/C++: 1:128

## Specifications

Function	
Forwarding capability	40 Gbit/s
T-CONTs per PON port	1024
Service flows per PON board	16368
Maximum frame size	2052 bytes
Maximum number of MAC addresses	16384
Maximum distance difference between two ONUs under the same PON port (board capability)	40 km
FEC	Bidirection
CAR group	Supported
HQoS	Not supported
Variable-length OMCI	Supported
ONU-based shaping or queue-based shaping	Supported
Type B protection (dual-homing)	Not supported
Type B protection (single-homing)	Supported
Type C protection (dual-homing)	Not supported
Type C protection (single-homing)	Supported
1588v2	Not supported
Rogue ONT detection and isolation	Supported
Automatic shutdown at high temperature	Supported
Energy saving for service boards	Supported
D-CCAP	Not supported
Environment	
Operating temperature	-40° C to +65° C
Power consumption	Static: 20 W Maximum: 46 W